

AP-S200/AP-S450/AP-300/AP-550/AP-750 MIDI Implementation

CASIO COMPUTER CO., LTD.

Contents

I	Overview	3
1	Product Configuration as a MIDI Device	3
1.1	System Section	3
1.2	Performance Controller Section	3
1.3	Sound Generator Section	3
2	About the Timbre Type	5
3	Controlling Send/Receive of MIDI Messages in Each Instrument Part	5
4	Conditions that Disable Message Send and Receive	5
II	Channel Message	6
5	Note Off	6
6	Note On	6
7	Control Change	7
7.1	Bank Select (00H,20H)	7
7.2	Modulation wheel or lever (01H)	7
7.3	Portamento Time (05H)	8
7.4	Data Entry (06H,26H)	8
7.5	Volume (07H)	8
7.6	Pan (0AH)	8
7.7	Expression Controller (0BH)	9
7.8	Damper pedal (Sustain) (40H)	9
7.9	Portamento On/Off (41H)	9
7.10	Sostenuto (42H)	10
7.11	Soft Pedal (43H)	10
7.12	Filter Resonance (47H)	10
7.13	Release Time (48H)	10
7.14	Attack Time (49H)	11
7.15	Filter Cutoff Frequency (4AH)	11
7.16	Vibrato Rate (4CH)	11
7.17	Vibrato Depth (4DH)	11
7.18	Vibrato Delay (4EH)	12

7.19	Portamento Control (54H)	12
7.20	High Resolution Velocity Prefix (58H)	12
7.21	Reverb Send Level (5BH)	12
7.22	Chorus Send Level (5DH)	13
7.23	Delay Send Level (5EH)	13
7.24	RPN (Registered Parameter Number) LSB/MSB (64H,65H)	13
7.25	All Sound Off (78H)	14
7.26	Reset All Controllers (79H)	14
7.27	All Notes Off (7BH)	14
7.28	Omni Mode Off (All Notes Off) (7CH)	15
7.29	Omni Mode On (All Notes Off) (7DH)	15
7.30	Mono Mode On (Poly Mode Off) (All Notes Off) (7EH)	15
7.31	Poly Mode On (Mono Mode Off) (All Notes Off) (7FH)	15
8	Program Change	15
9	Channel Pressure (Aftertouch)	16
10	Pitch Bend Change	16
III	System Message	17
11	Active Sensing	17
12	System Exclusive Message	17
12.1	Universal Real Time System Exclusive Message	17
12.2	Universal Non Real Time System Exclusive Message	19
12.3	CASIO General System Exclusive	19
IV	Setting Values and Send/ Receive Values	21
13	Setting Value Tables	21
13.1	Off/On Setting Value Table	21
13.2	Damper(Sustain) Pedal Setting Value Table	21
13.3	Soft Pedal Setting Value Table	21
13.4	-64 - 0 - +63 Setting Value Table	22
13.5	Pan Setting Value Table	22
13.6	Fine Tuning Setting Value Table	23
13.7	Reverb Type Setting Value Table	23
13.8	Chorus Type Setting Value Table	23
13.9	Reverb Type (CASIO General System Exclusive) Setting Value Table	24
13.10	Chorus Type (CASIO General System Exclusive) Setting Value Table	24
V	MIDI Implementation Notation	25
14	Value Notation	25
14.1	Hexadecimal Notation	25

Part I

Overview

1 Product Configuration as a MIDI Device

As a MIDI device, this Instrument consists of the System Section, Sound Generator Section, and Performance Controller Section described below. Each of these sections can send and receive specific MIDI Messages in accordance with its function.

1.1 System Section

The System Section manages the Instrument status and user data.

1.2 Performance Controller Section

The Performance Controller Section performs keyboard play and controller operations, and generates performance messages. Basically, generated performance messages are sent to external destinations while also being transmitted to the Sound Generator Section. The channel number of the sent channel message is in accordance with the Instrument's MIDI setting. For details about the MIDI setting, see the Instrument's User's Guide.

1.3 Sound Generator Section

The Sound Generator Section mainly performs receive of performance information and sound source setting information. It consists of a common part that does not depend on the channel and a musical instrument part that is independent of each channel.

1.3.1 Sound Generator Common Block

The common block consists of system effects, master control, etc. These can be controlled by effect function, or general universal system exclusive messages.

1.3.2 Instrument Part Block

The instrument part section is divided into A, B, C group for every 16 parts, and it consists of a total of 48 parts. The settings of each part can be changed using channel messages. Of these, only the C group can be controlled by external channel messages.

The functions assigned to each part are shown below.

Port	Part number	MIDI Receive Ch	MIDI Transmit ch	Assigned Function	Details
A	01	-	1-16	Upper1	-
A	02	-	1-16	Upper2	-
A	03	-	1-16	Lower1	-
A	04	-	-	-	-
A	05	-	-	-	-
A	06	-	-	-	-
A	07	-	-	-	-
A	08	-	-	Metronome	-
A	09	-	-	-	-
A	10	-	-	-	-
A	11	-	-	-	-
A	12	-	-	-	-
A	13	-	-	-	-
A	14	-	-	-	-
A	15	-	-	-	-
A	16	-	-	-	-

Port	Part number	MIDI Receive Ch	MIDI Transmit Ch	Assigned Function	Details
B	17	-	-	Recorder	System Track Upper1
B	18	-	-	Recorder	System Track Upper2
B	19	-	-	Recorder	System Track Lower1
B	20	-	-	-	-
B	21	-	-	-	-
B	22	-	-	-	-
B	23	-	-	-	-
B	24	-	-	Precount	-
B	25	-	-	-	-
B	26	-	-	-	-
B	27	-	-	-	-
B	28	-	-	-	-
B	29	-	-	-	-
B	30	-	-	-	-
B	31	-	-	-	-
B	32	-	-	-	-

Port	Part number	MIDI Receive Ch	MIDI Transmit Ch	Assigned Function	Details
C	33	1	-	MIDI/Song Play/Recorder	Recorder Solo Track
C	34	2	-	MIDI/Song Play	-
C	35	3	-	MIDI/Song Play	-
C	36	4	-	MIDI/Song Play	-
C	37	5	-	MIDI/Song Play	-
C	38	6	-	MIDI/Song Play	-
C	39	7	-	MIDI/Song Play	-
C	40	8	-	MIDI/Song Play	-
C	41	9	-	MIDI/Song Play	-
C	42	10	-	MIDI/Song Play	-
C	43	11	-	MIDI/Song Play	-
C	44	12	-	MIDI/Song Play	-
C	45	13	-	MIDI/Song Play	-
C	46	14	-	MIDI/Song Play	-
C	47	15	-	MIDI/Song Play	-
C	48	16	-	MIDI/Song Play	-

2 About the Timbre Type

Tones that are selected by each Instrument part have an attribute that depends on the sound source operation type. This attribute is called the “Timbre Type”, which is one of the types described below.

- LM (Linear Morphing) Piano

This Timbre Type is for Linear Morphing piano tones. The decay rate of the voice being sounded and Damper Resonance effect characteristics are seamlessly altered in accordance with the depressed amount of damper pedal. The method for producing sound in response to the note messages also is different from that of the melody Timbre Type, and operation is optimized for piano.

- Melody

This Timbre Type optimizes for normal melody tones. The damper pedal performs on/off operations.

For information about tone selection, see “8 Program Change.”

3 Controlling Send/Receive of MIDI Messages in Each Instrument Part

Send and receive of MIDI messages for each instrument part can be controlled by global Instrument MIDI settings and Instrument-specific system exclusive messages. See the Instrument’s User’s Guide for details.


4 Conditions that Disable Message Send and Receive

No MIDI messages at all can be sent or received while the instrument is starting up, shutting down, or accessing flash memory, etc.

Part II

Channel Message

Instrument Velocity Resolution The upper seven bits of the 14-bit resolution correspond to the Note On/Off message, while the lower seven bits correspond to the High Resolution Velocity Prefix message.



The initial default value for the lower 7 bits is 00H. Receipt of a High Resolution Prefix message causes the lower seven bits to be set, but note on is not performed.

Receipt of a Note On message causes the upper seven bits to be set with note on performed with 14-bit resolution Velocity.

The High Resolution Velocity Prefix message corresponds the message immediately following the Note On/Off message, and the lower seven bits are cleared to 00H immediately following note on by the Note On/Off message. 7-bit resolution note on using only the Note On/Off message also continues to be supported.

For details about each message, see "5 Note Off", "6 Note On" and "7.20 High Resolution Velocity Prefix".

5 Note Off

Format

Message Format: 8nH kkH vvH
9nH kkH 00H(receive only)

n: MIDI Channel Number

kk: Key Number

vv: Velocity

Transmit Sent when something is played on the keyboard. The key number changes in accordance with on the Transpose function and Octave Shift function. For Note Off Velocity, The AP-S200/AP-300 can only send a fixed value of 40H. However, S450/AP-550/AP-750 can send a value ranging from 00H to 7FH.

Receive Receipt stops a note being sounded by a note on message.

When a High Resolution Velocity Prefix message is received immediately prior to the Note Off message and the lower seven bits of the 14-bit Velocity are set, the 14-bit resolution note off is performed.

For information about the relationship between the Note Off message and High Resolution Velocity Prefix message, see "Instrument Velocity Resolution" at the beginning of part II.

6 Note On

Message Format: 9nH kkH vvH

n: MIDI Channel Number
kk: Key Number
vv: Velocity

Transmit Sent when something is played on the keyboard. The key number changes in accordance with on the Transpose function and Octave Shift function.

Receive Receipt sounds a note of the corresponding instrument part.

When a High Resolution Velocity Prefix message is received immediately prior to the Note On message and the lower seven bits of the 14-bit Velocity are set, the 14-bit resolution note on is performed.

For information about the relationship between the Note On message and High Resolution Velocity Prefix message, see "Instrument Velocity Resolution" at the beginning of part II.

7 Control Change

Message Format: BnH ccH vvH

n: MIDI Channel Number
cc: Control Number
vv: Value

For details about messages, see each section of this manual that covers them.

7.1 Bank Select (00H,20H)

Message Format: BnH 00H mmH (MSB)
BnH 20H llH (LSB)

n: MIDI Channel Number
mm: MSB Value(Note1)
ll: LSB Value(Transmit:00H, Receive:Ignored)

Note1: For details about the relationship between the MSB value and the tone, see the Tone List that comes with the Instrument's User's Guide.

Transmit Sent when a tone setup number is selected.

Receive Receipt causes a change in the tone bank number stored in Instrument memory, but the tone is not actually changed until a Program Change message is received. For details, see "8 Program Change".

7.2 Modulation wheel or lever (01H)

Message Format: BnH 01H vvH

n: MIDI Channel Number
vv: Value

Receive Receipt adds, to the tone being sounded, modulation of a depth specified by the value. In the case of a tone that already has modulation applied, receipt of this message increases the modulation depth. The modulation effect differs according to the tone being used.

7.3 Portamento Time (05H)

Message Format: BnH 05H vvH

n: MIDI Channel Number
vv: Value

Receive Receipt changes the portamento application time.

7.4 Data Entry (06H,26H)

Message Format: BnH 06H mmH (MSB)
BnH 26H 11H (LSB)

n: MIDI Channel Number
mm: MSB Value
11: LSB Value

Transmit Sent when there is a change to the parameter assigned to RPN.

Receive Receipt changes the parameter assigned to RPN.

7.5 Volume (07H)

Message Format: BnH 07H vvH

n: MIDI Channel Number
vv: Value

Transmit Sent when part volume is changed.

Receive Receipt changes the part volume.

7.6 Pan (0AH)

Message Format: BnH 0AH vvH

n: MIDI Channel Number
vv: Value(Note1)

Note1: For information about the relationship between setting values and send/receive values, see "13.5 Pan Setting Value Table" in "IV Setting Values and Send/Receive Values".

Receive Receipt changes the pan of the corresponding part.

7.7 Expression Controller (0BH)

Message Format: BnH 0BH vvH

n: MIDI Channel Number
vv: Value

Receive Receipt changes the Expression value.

7.8 Damper pedal (Sustain) (40H)

Message Format: BnH 40H vvH

n: MIDI Channel Number
vv: Value

Transmit Sent when a pedal that has a damper(sustain) function is operated.

Receive Receipt performs an operation equivalent to a damper(sustain) pedal operation.

Timbre Type Specific Operation This operation differs in accordance with the Timbre Type (see “2 About the Timbre Type”) setting.

- LM Piano
Continuous control of the following is performed in accordance with the value of the received message.
 - Piano note decay rate
 - Resonance characteristics and decay rate of Damper Resonance effectsee “13.2 Damper(Sustain) Pedal Setting Value Table” in “IV Setting Values and Send/Receive Values.”
- Melody
damper(sustain) off/on control is performed in accordance with the value of the received message. For information about the relationship between setting values and send/receive values, see the “13.1 Off/On Setting Value Table” in “IV Setting Values and Send/Receive Values”.

7.9 Portamento On/Off (41H)

Message Format: BnH 41H vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.1 Off/On Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Receive Receipt changes the portamento on/off setting.

7.10 Sostenuto (42H)

Message Format: BnH 42H vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.1 Off/On Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Transmit Sent when a pedal that has a sostenuto function is operated.

Receive Receipt performs an operation equivalent to a sostenuto pedal operation.

7.11 Soft Pedal (43H)

Message Format: BnH 43H vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.3 Soft Pedal Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Transmit Sent when a pedal that has a soft function is operated.

Receive Receipt performs an operation equivalent to a soft pedal operation.

7.12 Filter Resonance (47H)

Message Format: BnH 47H vvH

n: MIDI Channel Number
vv: Value

Receive Receipt changes the filter resonance intensity.

7.13 Release Time (48H)

Message Format: BnH 48H vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.4 -64 - 0 - +63 Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Receive Receipt makes a relative change in the time it takes for a note to decay to zero after a key is released.

7.14 Attack Time (49H)

Message Format: BnH 49H vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.4 -64 - 0 - +63 Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Receive Receipt makes a relative change in the time it takes for a note to rise to its maximum level.

7.15 Filter Cutoff Frequency (4AH)

Message Format: BnH 4AH vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.4 -64 - 0 - +63 Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Receive Receipt changes the filter cutoff frequency.

7.16 Vibrato Rate (4CH)

Message Format: BnH 4CH vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.4 -64 - 0 - +63 Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Receive Receipt changes the note vibrato rate.

7.17 Vibrato Depth (4DH)

Message Format: BnH 4DH vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.4 -64 - 0 - +63 Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Receive Receipt changes the depth of pitch modulation.

7.18 Vibrato Delay (4EH)

Message Format: BnH 4EH vvH

n: MIDI Channel Number
vv: Value (Note1)

Note1: For information about the relationship between setting values and send/receive values, see the “13.4 -64 - 0 - +63 Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Receive Receipt changes the time it takes until note vibrato starts.

7.19 Portamento Control (54H)

Message Format: BnH 54H vvH

n: MIDI Channel Number
vv: Source Key Number

Receive Receipt of this message first stores the Source Note Number for the next note. When the next Note On is received, the portamento effect is applied to the note using this Source Note Number as the pitch start point and the Note On event key number as the end point. If there already is a note being sounded by Source Note Number at this time, the new note on is not performed and the portamento effect is applied to the pitch of the note being sounded. That is to say that legato play is performed.

7.20 High Resolution Velocity Prefix (58H)

Message Format: BnH 58H vvH

n: MIDI Channel Number
vv: Value

Transmit When High Resolution Velocity MIDI Out of this unit’s MIDI setting is On, sends the lower seven bits of 14-bit Velocity when a key is pressed or released (For AP-S200/AP-300, High Resolution Velocity Prefix is not sent when the key is released).

Receive Receipt is handled, in combination with the following Note On/Off message, as the lower seven bits of 14-bit Velocity.

For information about the relationship between the Note On/Off message and High Resolution Velocity Prefix message, see “Instrument Velocity Resolution” at the beginning of part II.

7.21 Reverb Send Level (5BH)

Message Format: BnH 5BH vvH

n: MIDI Channel Number
vv: Value

Receive Receipt changes the reverb send of the corresponding part.

7.22 Chorus Send Level (5DH)

Message Format: BnH 5DH vvH

n: MIDI Channel Number
vv: Value

Receive Receipt changes the chorus send of the corresponding part.

7.23 Delay Send Level (5EH)

Message Format: BnH 5EH vvH

n: MIDI Channel Number
vv: Value

Receive Receipt changes the delay send of the corresponding part.

7.24 RPN (Registered Parameter Number) LSB/MSB (64H,65H)

Message Format: BnH 64H 11H (LSB)
BnH 65H mmH (MSB)

n: MIDI Channel Number
11: LSB Value
mm: MSB Value

7.24.1 Pitch Bend Sensitivity

Message Format: BnH 64H 00H
BnH 65H 00H
BnH 06H mmH
BnH 26H 11H

n: MIDI Channel Number
mm: MSB Value(00H - 18H)
11: LSB Value(Transmit:00H, Receive:Ignored)

Receive Receipt changes Bend Range of the corresponding part.

7.24.2 Channel Fine Tuning

Message Format: BnH 64H 01H
BnH 65H 00H
BnH 06H mmH
BnH 26H 11H

n: MIDI Channel Number
mm: MSB Value
11: LSB Value

Transmit Sent with data entry LSB and MSB when the fine tuning of the part is changed.

Receive Receipt changes the fine tuning of the corresponding part.

7.24.3 Channel Coarse Tuning

Message Format: BnH 64H 02H
 BnH 65H 00H
 BnH 06H mmH
 BnH 26H 11H

n: MIDI Channel Number
mm: MSB Value(28H - 58H)
ll: LSB Value(Transmit:00H, Receive:Ignored)

Receive Receipt changes the coarse tune of the corresponding part.

7.24.4 RPN NULL

Message Format: BnH 64H 7FH
 BnH 65H 7FH

n: MIDI Channel Number

Receive Receipt de-selects RPN.

7.25 All Sound Off (78H)

Message Format: BnH 78H 00H

n: MIDI Channel Number

Receive Receipt stops all voices that are sounding.

7.26 Reset All Controllers (79H)

Message Format: BnH 79H 00H

n: MIDI Channel Number

Receive Receipt initializes each performance controller.

7.27 All Notes Off (7BH)

Message Format: BnH 7BH 00H

n: MIDI Channel Number

Receive Receipt releases (key release) all voices that are sounding.

7.28 Omni Mode Off (All Notes Off) (7CH)

Message Format: BnH 7CH 00H

n: MIDI Channel Number

Receive Receipt performs the same operation as when All Notes Off is received.

7.29 Omni Mode On (All Notes Off) (7DH)

Message Format: BnH 7DH 00H

n: MIDI Channel Number

Receive Receipt performs the same operation as when All Notes Off is received.

7.30 Mono Mode On (Poly Mode Off) (All Notes Off) (7EH)

Message Format: BnH 7EH 00H

n: MIDI Channel Number

Receive Receipt performs the same operation as when All Notes Off is received.

7.31 Poly Mode On (Mono Mode Off) (All Notes Off) (7FH)

Message Format: BnH 7FH 00H

n: MIDI Channel Number

Receive Receipt performs the same operation as when All Notes Off is received.

8 Program Change

Message Format: CnH ppH

n: MIDI Channel Number

pp: Program Number (Note1)

Note1: For details about the relationship between the program number and the tone, see the Tone List that comes with the Instrument's User's Guide.

Transmit Sent when a tone number is selected.

Receive Receipt changes the tone of the corresponding part. The selected tone is determined by the program value of this message and the Bank Select message value received prior to this message. Also note that receipt of this message also may change the Timbre Type that corresponds to the selected tone. For more information, see "2 About the Timbre Type" below.

9 Channel Pressure (Aftertouch)

Message Format: DnH vvH

n: MIDI Channel Number
vv: Value

Receive Receipt adds, to the tone being sounded, modulation of a depth specified by the value. In the case of a tone that already has modulation applied, receipt of this message increases the modulation depth. The modulation effect differs according to the tone being used.

10 Pitch Bend Change

Message Format: EnH llH mmH

n: MIDI Channel Number
ll: Value LSB
mm: Value MSB

Receive Receipt changes the pitch of the currently sounding note. The range of the pitch change depends on the Pitch Bend Sensitivity value setting in RPN. For information about the Pitch Bend Sensitivity, see the “7.24.1 Pitch Bend Sensitivity” of this document.

Part III

System Message

11 Active Sensing

Message Format: FEH

Receive Once this message is received, the Active Sensing mode is entered. If no MIDI message is received for a specified amount of time, voices being sounded by this Instrument's sound source are released, the controller is reset, and the Active Sensing mode is exited.

12 System Exclusive Message

Message Format: FOH iiH 7FH...F7H

ii: ID Number

The Instrument sends and receives standard universal system exclusive messages, and system exclusive messages that have Instrument-specific formats (CASIO General System Exclusive).

ID Number The ID numbers handed by this Instrument are shown below.

ID Number	ID Name
-----------	---------

44H	Casio Computer Co. Ltd
7EH	Non Real Time System Exclusive Message
7FH	Real Time System Exclusive Message

12.1 Universal Real Time System Exclusive Message

Message Format: FOH 7FH 7FH...F7H

12.1.1 Master Volume

Message Format: FOH 7FH 7FH 04H 01H 11H mmH F7H

11: LSB Value(Receive:Ignored)
mm: MSB Value

Receive Receipt changes the master volume.

12.1.2 Master Fine Tuning

Message Format: FOH 7FH 7FH 04H 03H 11H mmH F7H

11: LSB Value(Note1)
mm: MSB Value(Note1)

Note1: For information about the relationship between setting values and send/receive values, see "13.6 Fine Tuning Setting Value Table" in "IV Setting Values and Send/Receive Values" of this document.

Transmit This message is sent when the tuning setting is changed.

Receive Receipt changes the tuning setting.

12.1.3 Master Coarse Tuning

Message Format: FOH 7FH 7FH 04H 04H 11H mmH F7H

11: LSB Value(Transmit:00H,Receive:Ignored)
mm: MSB Value(28H - 58H)

Receive Receipt changes the the master coarse tuning parameter.

12.1.4 Reverb Type

Message Format: FOH 7FH 7FH 04H 05H 01H 01H 01H 01H 01H 00H vvH F7H

vv: Value(Note1)

Note1: For information about the relationship between setting values and send/receive values, see "13.7 Reverb Type Setting Value Table" in "IV Setting Values and Send/Receive Values" of this document.

Receive Receipt changes the reverb type.

12.1.5 Reverb Time

Message Format: FOH 7FH 7FH 04H 05H 01H 01H 01H 01H 01H 01H vvH F7H

vv: Value

Receive Receipt changes the reverb time.

12.1.6 Chorus Type

Message Format: FOH 7FH 7FH 04H 05H 01H 01H 01H 01H 02H 00H vvH F7H

vv: Value(Note1)

Note1: For information about the relationship between setting values and send/receive values, see "13.8 Chorus Type Setting Value Table" in "IV Setting Values and Send/Receive Values" of this document.

Receive Receipt changes the chorus type.

12.1.7 Modulation Rate

Message Format: FOH 7FH 7FH 04H 05H 01H 01H 01H 01H 02H 01H vvH F7H

vv: Value

Receive Receipt changes the chorus rate.

12.1.8 Modulation Depth

Message Format: FOH 7FH 7FH 04H 05H 01H 01H 01H 01H 02H 02H vvH F7H
vv: Value

Receive Receipt changes the chorus level setting.

12.1.9 Send To Reverb

Message Format: FOH 7FH 7FH 04H 05H 01H 01H 01H 01H 02H 04H vvH F7H
vv: Value

Receive Receipt changes the chorus sent to reverb setting.

12.2 Universal Non Real Time System Exclusive Message

Message Format: FOH 7EH 7FH...F7H

12.2.1 GM System On

Message Format: FOH 7EH 7FH 09H 01H F7H

Receive Receipt changes the sound source to the GM default state.

12.2.2 GM System Off

Message Format: FOH 7EH 7FH 09H 02H F7H

Receive Receipt changes the sound source setting to the Instrument presetting.

12.2.3 GM2 System On

Message Format: FOH 7EH 7FH 09H 03H F7H

Receive Though the Instrument does not support GM2, receipt of the GM2 System On message has the same result as receipt of the GM System On message.

12.3 CASIO General System Exclusive

Message Format: FOH 44H 7EH 7FH iiH ccH ssH ggH ppH ddH ... F7H

ii: Device ID (7FH)
cc: Category ID
ss: Sub Category ID
gg: Group ID (00H)
pp: Parameter ID
dd ...: Data

This message can be used to perform sound source parameter operations.

12.3.1 Reverb Type

Message Format: F0H 44H 7EH 7FH 7FH 04H 00H 00H 00H 00H ttH F7H

tt: Type(Note1)

Note1: For information about the relationship between setting values and send/receive values, see “13.9 Reverb Type (CASIO General System Exclusive) Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Transmit Sent when hall simulator/reverb type is changed.

Receive Receipt changes the reverb type.

12.3.2 Chorus Type

Message Format: F0H 44H 7EH 7FH 7FH 04H 01H 00H 00H 00H ttH F7H

tt: Type(Note1)

Note1: For information about the relationship between setting values and send/receive values, see “13.10 Chorus Type (CASIO General System Exclusive) Setting Value Table” in “IV Setting Values and Send/Receive Values” of this document.

Transmit Sent when chorus type is changed.

Receive Receipt changes the chorus type.

Part IV

Setting Values and Send/ Receive Values

13 Setting Value Tables

13.1 Off/On Setting Value Table

Transmit Value	Receive Value	Parameter
00H	00H - 3FH	Off
7FH	40H - 7FH	On

13.2 Damper(Sustain) Pedal Setting Value Table

AP-S200/AP-300

Transmit Value	Receive Value	Parameter
00H	00H - 3FH	Off
40H	40H - 65H	Half
7FH	66H - 7FH	On

AP-S450/AP-550/AP-750

Transmit Value	Receive Value	Parameter
00H	00H	Off
:	:	(continuous)
7FH	7FH	Full

13.3 Soft Pedal Setting Value Table

AP-S200/AP-S450

Transmit Value	Receive Value	Parameter
00H	00H - 3FH	Off
7FH	40H - 7FH	On

AP-300/AP-550

Transmit Value	Receive Value	Parameter
00H	00H - 3FH	Off
40H	40H - 65H	Half
7FH	66H - 7FH	On

AP-750

Transmit Value	Receive Value	Parameter
00H	00H	Off
:	:	(continuous)
7FH	7FH	Full

13.4 -64 - 0 - +63 Setting Value Table

Transmit Value	Receive Value	Parameter
00H	00H	-64
:	:	:
40H	40H	0
:	:	:
7FH	7FH	+63

13.5 Pan Setting Value Table

Transmit Value	Receive Value	Parameter
00H	00H	Left
:	:	:
40H	40H	Center
:	:	:
7FH	7FH	Right

13.6 Fine Tuning Setting Value Table

Transmit Value	Receive Value	Parameter
(LSB, MSB)		
(43H, 00H)	(00H, 00H) - (5FH, 00H)	415.5 Hz
(65H, 00H)	(60H, 00H) - (7FH, 00H)	415.6 Hz
(07H, 01H)	(00H, 01H) - (1FH, 01H)	415.7 Hz
(29H, 01H)	(20H, 01H) - (3FH, 01H)	415.8 Hz
:	:	:
(40H, 3FH)	(30H, 3FH) - (4FH, 3FH)	439.8 Hz
(60H, 3FH)	(50H, 3FH) - (6FH, 3FH)	439.9 Hz
(00H, 40H)	(70H, 3FH) - (1FH, 40H)	440.0 Hz
(20H, 40H)	(20H, 40H) - (3FH, 40H)	440.1 Hz
(40H, 40H)	(40H, 40H) - (5FH, 40H)	440.2 Hz
:	:	:
(54H, 7EH)	(50H, 7EH) - (6FH, 7EH)	465.6 Hz
(73H, 7EH)	(70H, 7EH) - (0FH, 7FH)	465.7 Hz
(11H, 7FH)	(10H, 7FH) - (2FH, 7FH)	465.8 Hz
(30H, 7FH)	(30H, 7FH) - (7FH, 7FH)	465.9 Hz

13.7 Reverb Type Setting Value Table

Transmit Value	Receive Value	Parameter
-	00H	Small Room
-	01H	Medium Room
-	02H	Large Room
-	03H	Medium Hall
-	04H	Large Hall
-	08H	Plate

13.8 Chorus Type Setting Value Table

Transmit Value	Receive Value	Parameter
-	00H	Chorus1
-	01H	Chorus2
-	02H	Chorus3
-	03H	Chorus4
-	04H	FB Chorus
-	05H	Flanger

13.9 Reverb Type (CASIO General System Exclusive) Setting Value Table

Transmit Value	Receive Value	Parameter	Category	Description
00H	00H	Room1	Reverb	
01H	01H	Room2	Reverb	AP-S450/AP-550/AP-750 only
02H	02H	Room3	Reverb	AP-S450/AP-550/AP-750 only
03H	03H	Hall1	Reverb	
04H	04H	Hall2	Reverb	AP-S450/AP-550/AP-750 only
0AH	0AH	Large Room	Reverb	
0CH	0CH	Stadium	Reverb	
17H	17H	Hall3	Reverb	AP-S450/AP-550/AP-750 only
20H	20H	Off	Reverb	
21H	21H	NY Club	Hall Simulator	
22H	22H	Scoring Stage	Hall Simulator	AP-750 only
25H	25H	Opera Hall	Hall Simulator	
26H	26H	Viennese Hall	Hall Simulator	AP-750 only
27H	27H	L.A. Hall	Hall Simulator	AP-750 only
28H	28H	Berlin Hall	Hall Simulator	
2AH	2AH	British Stadium	Hall Simulator	
2CH	2CH	Salon	Hall Simulator	AP-750 only
2DH	2DH	Tone	Reverb	AP-750 only

13.10 Chorus Type (CASIO General System Exclusive) Setting Value Table

Transmit Value	Receive Value	Parameter	Description
00H	00H	Chorus1 (Light Chorus)	
01H	01H	Chorus2	AP-750 only
02H	02H	Chorus3 (Chorus)	
03H	03H	Chorus4	AP-750 only
04H	04H	FB Chorus	AP-750 only
05H	05H	Flanger4	AP-750 only
06H	06H	Flanger3	AP-750 only
07H	07H	Flanger2 (Flanger)	
08H	08H	Flanger1	AP-750 only
09H	09H	Short Delay1	AP-750 only
0AH	0AH	Short Delay2	AP-750 only
0FH	0FH	Deep Chorus	
10H	10H	Tone	

Part V

MIDI Implementation Notation

14 Value Notation

14.1 Hexadecimal Notation

MIDI implementation sometimes requires that data be expressed in hexadecimal format. Hexadecimal values are indicated by the letter “H” after the value. The hexadecimal equivalents of decimal values 10 through 15 are expressed as the letters A through F.

The table below shows the hexadecimal equivalents for decimal values 0 through 127, which are often used in MIDI messages.

Decimal	Hexadecimal	Decimal	Hexadecimal	Decimal	Hexadecimal	Decimal	Hexadecimal
0	00H	32	20H	64	40H	96	60H
1	01H	33	21H	65	41H	97	61H
2	02H	34	22H	66	42H	98	62H
3	03H	35	23H	67	43H	99	63H
4	04H	36	24H	68	44H	100	64H
5	05H	37	25H	69	45H	101	65H
6	06H	38	26H	70	46H	102	66H
7	07H	39	27H	71	47H	103	67H
8	08H	40	28H	72	48H	104	68H
9	09H	41	29H	73	49H	105	69H
10	0AH	42	2AH	74	4AH	106	6AH
11	0BH	43	2BH	75	4BH	107	6BH
12	0CH	44	2CH	76	4CH	108	6CH
13	0DH	45	2DH	77	4DH	109	6DH
14	0EH	46	2EH	78	4EH	110	6EH
15	0FH	47	2FH	79	4FH	111	6FH
16	10H	48	30H	80	50H	112	70H
17	11H	49	31H	81	51H	113	71H
18	12H	50	32H	82	52H	114	72H
19	13H	51	33H	83	53H	115	73H
20	14H	52	34H	84	54H	116	74H
21	15H	53	35H	85	55H	117	75H
22	16H	54	36H	86	56H	118	76H
23	17H	55	37H	87	57H	119	77H
24	18H	56	38H	88	58H	120	78H
25	19H	57	39H	89	59H	121	79H
26	1AH	58	3AH	90	5AH	122	7AH
27	1BH	59	3BH	91	5BH	123	7BH
28	1CH	60	3CH	92	5CH	124	7CH
29	1DH	61	3DH	93	5DH	125	7DH
30	1EH	62	3EH	94	5EH	126	7EH
31	1FH	63	3FH	95	5FH	127	7FH

CASIO®